

PORTABLE RM 100

Your expertise
closer to
the product



No matter where, the RM100 PORTABLE allows you to bring your viscosity measurement methods where your lab can not operate. With programming, memorization, temperature measurement and all measuring systems, all your expertise is moving!

FEATURES AND BENEFITS

- Autonomy more than one hour.
- Charge indicator.
- Huge speed and torque range.
- Usable with standard or rack stand (option).
- Programming and recording method.
- Direct measure with time to stop.
- User and locked mode.
- Data recording and USB transfer.
- Torque gage on display.
- Integrated temperature probe.
- Printer connection.
- Compatible with RheoTex software.
- Display of viscosity limits according to mobile and speed.
- Speed or shear rate control.

WHAT'S INCLUDED WITH DEVICE ?

- 1 Integrated temperature probe .
- 1 Carrying case (p68).
- 1 Touch screen stylus.
- 1 User manual.
- 1 Calibration and checking certificate.
- 1 Microfiber cloth.
- 1 Harness.

AVAILABLE INSTRUMENT

Reference	Designation	Viscosity range (mPa.s)
T100100	RM100 PORTABLE VISCOMETER	200(1**) to 240M*

M for million / * With MS-RV (RV2 to RV7) (p75). Not included. / ** Can reach 1 mPa.s with MS DIN19 (p72). Not included.

SPECIFICATIONS

Type of instrument

Rotating springless viscometer with 7" Touch screen

Rotation speeds

Unlimited number of speeds between 0.3 and 1500 rpm

Torque range

From 0.05 to 30 mNm

Temperature Probe

Equipped with a PT100 sensor which indicates temperatures between -50°C to +300°C

Accuracy

+/- 1 % of the full scale

Repeatability

+/- 0,2 %

Display

Viscosity (cP/Poises or mPa.s / Pa.s)

Speed – Shear rate – Torque – %- Shear stress - Time
– Temperature**Norms**

ASTM : D115 ; D789 ; D1076 ; D1084 ; D1337 ;
 D1338 ; D1417; D1439 ; D1824 ; D2196 ; D2243 ;
 D2364 ; D2556 ; D3288 ; D3468 ; D3716 ; D3730 ;
 D3794 ; D4016 ; D4143 ; D4878 ; D4889 ; D5324
 ; D5400 ; D6279 ; D6577 ; D7394 ; D8020 ; E2975
 ; F1607 ; **BS** 5350 ; **DIN** 2555 ; 3219 ; 52007-1 ;
 53019-1; 54453 ; **EN** 302-7 ; 2555 ; 3219 ; 10301 ;
 12092 ; 12802 ; 15425 ; 15564 ; **ISO** 1652 ; 2555 ;
 2884-2 ; 3219 ; 10364-12

Languages

French/English/Russian/Spanish/Turkish/German

Supply voltage

90-240 VAC 50/60 Hz

Analog output

4 – 20 mA

PC connections

RS232 Port and USB

Printer connectionUSB Host Port -
Compatible PCL/5**Dimensions and weight**

Head : Ø 90 mm

Box D60 x H260 x W120

Weight: 2 kg

COMPATIBLES

MEASURING SYSTEMS

MS-RV (p75), **MS-LV** (p75), **MS-BV** (p76),
MS-VANES (p77), **MS-KREBS** (p77), **MS-SV** (p79),
MS-ULV (p78), **MS-DIN** (p72), **MS-R** (p74).

COMPATIBLES

TEMPERATURE CONTROLS

EVA LR (p60), **EVA MS DIN** (p58),
RT-1 PLUS (p61), **EVA MS-R** (p59).

OPTIONS & ACCESSORIES



- Standard or rack stand (p68).
- HELIPRO stand (p66).
- Small volume package (p67).
- THERMOCELL package (p61).
- Bayonet spindle rack (p69).
- Barcode reader with stand and cable (p68).
- Touch screen protector (p68).
- Viscosity standards oil (p69).
- Dymo printer (p68).
- RheoTex software (p64-65)

Tel : +33 (0)4 78 08 54 06
 Fax : +33 (0)4 78 08 69 44
 contact@lamyrheology.com

11 A, rue des Aulnes
 69410 Champagne au Mont d'Or
 France